



SPECIFICATIES VAN DE 2017 RAC LINE-UP

ARTCOOL Smart Inverter



Unit			9k	12k	18k
Binnendeel			AM09BP.NSJ	AM12BP.NSJ	AM18BP.NSK
Capaciteit	Koelen	Min / Nominaal / W Max	890/2500/3700	890/3500/4040	900/5000/5525
	Verwarmen +7°C	Min / Nominaal / W Max	890/3200/4100	890/3800/5100	900/5800/6438
S.E.E.R.			6.5	6.4	6.5
S.C.O.P.			4.0	4.0	4.0
Energie Label	Koelen / Verwarmen		A++ / A+	A++ / A+	A++ / A+
Geluidsniveau	Koelen	S/L/M/H dBA	19/27/35/41	19/27/35/41	31/34/39/44
	Verwarmen	S/L/M/H dBA	27/35/41	27/35/41	34/39/44
Afmetingen			mm	mm	mm
Netto gewicht			kg	kg	kg
Buitendeel			AM09BP.UA3	AM12BP.UA3	AM18BP.UL2
Geluidsniveau	Koelen	Hoog dBA	49	49	53
Afmetingen			mm	mm	mm

Bevat gefluoreerde broeikasgassen. R410a (GWP: 2088)
S: Slaapstand / L: Laag / M: Medium / H: Hoog

ARTCOOL Stylist Smart Inverter



Unit				9k	12k	
Binnendeel				G09WL.NS3	G12WL.NS3	
Capaciteit	Koelen	Min / Nominaal / Max	W	1300/2500/3500	1300/3500/4000	
	Verwarmen +7°C	Min / Nominaal / Max	W	1300/3000/4200	1300/3500/5000	
S.E.E.R.				5.70	5.60	
S.C.O.P.				3.80	3.80	
Energie Label Koelen / Verwarmen				A+ / A	A+ / A	
Geluidsniveau	Koelen	S/L/M/H	dBA	19/29/34/39	19/29/34/39	
	Verwarmen	S/L/M/H	dBA	32/35/39	32/35/39	
Afmetingen				mm	645*645*121	
Netto gewicht				kg	18	
Buitendeel				G09WL.UL2	G12WL.UL2	
Geluidsniveau Koelen				Hoog	dBA	45
Afmetingen				mm	770*545*288	

Prestige Smart Inverter



Unit				9k	12k	
Binnendeel				H09AL.NSM	H12AL.NSM	
Capaciteit	Koelen	Min / Nominaal / Max	W	300/2500/3800	300/3500/4040	
	Verwarmen +7°C	Min / Nominaal / Max	W	300/3200/6600	300/4000/6800	
S.E.E.R.				9.3	9.2	
S.C.O.P.				5.3	5.3	
Energie Label Koelen / Verwarmen				A+++ / A+++	A+++ / A+++	
Geluidsniveau	Koelen	S/L/M/H	dBA	17/25/33/39	17/25/33/39	
	Verwarmen	L/M/H	dBA	25/33/39	25/33/39	
Afmetingen				mm	875*295*235	
Netto gewicht				kg	11.5	
Buitendeel				H09AL.UE1	H12AL.UE1	
Geluidsniveau Koelen				Hoog	dBA	48
Afmetingen				mm	870*655*320	

Deluxe Smart Inverter



Unit				9k	12k	18k	24k	
Binnendeel				DM09RP.NSJ	DM12RP.NSJ	DM18RP.NSK	DM24RP.NSK	
Capaciteit	Koelen	Min / Nominaal / Max	W	890/2500/3700	890/3500/4040	900/5000/5525	900/6600/7420	
	Verwarmen +7°C	Min / Nominaal / Max	W	890/3200/5000	890/4000/6000	900/5800/6438	900/7500/8640	
S.E.E.R.				7.7	7.6	7.0	6.5	
S.C.O.P.				4.6	4.6	4.2	4.0	
Energie Label Koelen / Verwarmen				A++ / A++	A++ / A++	A++ / A+	A+ / A+	
Geluidsniveau	Koelen	S/L/M/H	dBA	19/24/35/40	19/24/35/40	31/34/39/44	31/34/42/47	
	Verwarmen	L/M/H	dBA	24/35/40	24/35/40	34/39/44	34/42/47	
Afmetingen				mm	837*302*189	837*302*189	998*330*210	
Netto gewicht				kg	8.3	8.3	12	
Buitendeel				DM09RP.UL2	DM12RP.UL2	DM18RP.UL2	DM24RP.UUE	
Geluidsniveau Koelen				Hoog	dBA	47	47	53
Afmetingen				mm	770*545*288	770*545*288	770*545*288	

Standard Plus Smart Inverter



Unit				9k	12k	18k	24k	
Binnendeel				PM09SP.NSJ	PM12SP.NSJ	PM18SP.NSK	PM24SP.NSK	
Capaciteit	Koelen	Min / Nominaal / Max	W	890/2500/3700	890/3500/4040	900/5000/5525	900/6600/7420	
	Verwarmen +7°C	Min / Nominaal / Max	W	890/3200/4100	890/3800/5100	900/5800/6438	900/7500/8640	
S.E.E.R.				6.5	6.4	6.5	6.2	
S.C.O.P.				4.0	4.0	4.0	3.9	
Energie Label Koelen / Verwarmen				A++ / A+	A++/A+	A++ / A+	A+ / A	
Geluidsniveau	Koelen	S/L/M/H	dBA	19/27/35/41	19/27/35/41	31/34/39/44	31/34/42/47	
	Verwarmen	L/M/H	dBA	27/35/41	27/35/41	34/39/44	34/42/47	
Afmetingen				mm	837*302*189	837*302*189	998*330*210	
Netto gewicht				kg	8,7	8,7	12	
Buitendeel				PM09SP.UA3	PM12SP.UA3	PM18SP.UL2	PM24SP.UUE	
Geluidsniveau Koelen				Hoog	dBA	49	49	53
Afmetingen				mm	717*483*230	717*483*230	770*545*288	

Bevat gefluoreerde broeikasgassen. R410a (GWP: 2088)
S: Slaapstand / L: Laag / M: Medium / H: Hoog