



SPECIFICATIES VAN DE 2017 RAC LINE-UP


ARTCOOL Smart Inverter



Unit				9k	12k	18k	
Binnendeel				AM09BP.NSJ	AM12BP.NSJ	AM18BP.NSK	
Capaciteit	Koelen	Min / Nominaal / W Max	890/2500/3700	890/3500/4040	900/5000/5525		
	Verwarmen +7°C	Min / Nominaal / W Max	890/3200/4100	890/3800/5100	900/5800/6438		
S.E.E.R.				6.5	6.4	6.5	
S.C.O.P.				4.0	4.0	4.0	
Energie Label	Koelen / Verwarmen		A++ / A+	A++ / A+	A++ / A+		
Geluidsniveau	Koelen	S/L/M/H	dBA	19/27/35/41	19/27/35/41	31/34/39/44	
	Verwarmen	S/L/M/H	dBA	27/35/41	27/35/41	34/39/44	
Afmetingen				mm	837*308*192	837*308*192	998*345*212
Netto gewicht				kg	9.9	9.9	13.2
Buitendeel				AM09BP.UA3	AM12BP.UA3	AM18BP.UL2	
Geluidsniveau	Koelen	Hoog	dBA	49	49	53	
Afmetingen				mm	717*483*230	717*483*230	770*545*288

Bevat gefluoreerde broeikasgassen. R410a (GWP: 2088)
S: Slaapstand / L: Laag / M: Medium / H: Hoog

ARTCOOL Stylist Smart Inverter




Unit				9k	12k
Binnendeel				G09WL.NS3	G12WL.NS3
Capaciteit	Koelen	Min / Nominaal / Max	W	1300/2500/3500	1300/3500/4000
	Verwarmen +7°C	Min / Nominaal / Max	W	1300/3000/4200	1300/3500/5000
S.E.E.R.				5.70	5.60
S.C.O.P.				3.80	3.80
Energie Label Koelen / Verwarmen				A+ / A	A+ / A
Geluidsniveau	Koelen	S/L/M/H	dB(A)	19/29/34/39	19/29/34/39
	Verwarmen	S/L/M/H	dB(A)	32/35/39	32/35/39
Afmetingen				mm	645*645*121
Netto gewicht				kg	18
Buitendeel				G09WL.UL2	G12WL.UL2
Geluidsniveau	Koelen	Hoog	dB(A)	45	45
	Afmetingen				mm

Prestige Smart Inverter



Unit				9k	12k
Binnendeel				H09AL.NSM	H12AL.NSM
Capaciteit	Koelen	Min / Nominaal / Max	W	300/2500/3800	300/3500/4040
	Verwarmen +7°C	Min / Nominaal / Max	W	300/3200/6600	300/4000/6800
S.E.E.R.				9.3	9.2
S.C.O.P.				5.3	5.3
Energie Label Koelen / Verwarmen				A+++ / A+++	A+++ / A+++
Geluidsniveau	Koelen	S/L/M/H	dB(A)	17/25/33/39	17/25/33/39
	Verwarmen	L/M/H	dB(A)	25/33/39	25/33/39
Afmetingen				mm	875*295*235
Netto gewicht				kg	11.5
Buitendeel				H09AL.UE1	H12AL.UE1
Geluidsniveau	Koelen	Hoog	dB(A)	48	48
	Afmetingen				mm

Deluxe Smart Inverter



Unit				9k	12k	18k	24k
Binnendeel				DM09RP.NSJ	DM12RP.NSJ	DM18RP.NSK	DM24RP.NSK
Capaciteit	Koelen	Min / Nominaal / Max	W	890/2500/3700	890/3500/4040	900/5000/5525	900/6600/7420
	Verwarmen +7°C	Min / Nominaal / Max	W	890/3200/5000	890/4000/6000	900/5800/6438	900/7500/8640
S.E.E.R.				7.7	7.6	7.0	6.5
S.C.O.P.				4.6	4.6	4.2	4.0
Energie Label Koelen / Verwarmen				A++ / A++	A++ / A++	A++ / A+	A++ / A+
Geluidsniveau	Koelen	S/L/M/H	dB(A)	19/24/35/40	19/24/35/40	31/34/39/44	31/34/42/47
	Verwarmen	L/M/H	dB(A)	24/35/40	24/35/40	34/39/44	34/42/47
Afmetingen				mm	837*308*189	837*308*189	998*345*210
Netto gewicht				kg	8.3	8.3	12
Buitendeel				DM09RP.UL2	DM12RP.UL2	DM18RP.UL2	DM24RP.UUE
Geluidsniveau	Koelen	Hoog	dB(A)	47	47	53	56
	Afmetingen				mm	770*545*288	770*545*288

Standard Plus Smart Inverter



Unit				9k	12k	18k	24k
Binnendeel				PM09SP.NSJ	PM12SP.NSJ	PM18SP.NSK	PM24SP.NSK
Capaciteit	Koelen	Min / Nominaal / Max	W	890/2500/3700	890/3500/4040	900/5000/5525	900/6600/7420
	Verwarmen +7°C	Min / Nominaal / Max	W	890/3200/4100	890/3800/5100	900/5800/6438	900/7500/8640
S.E.E.R.				6.5	6.4	6.5	6.2
S.C.O.P.				4.0	4.0	4.0	3.9
Energie Label Koelen / Verwarmen				A++ / A+	A++/A+	A++ / A+	A++ / A
Geluidsniveau	Koelen	S/L/M/H	dB(A)	19/27/35/41	19/27/35/41	31/34/39/44	31/34/42/47
	Verwarmen	L/M/H	dB(A)	27/35/41	27/35/41	34/39/44	34/42/47
Afmetingen				mm	837*308*189	837*308*189	998*345*210
Netto gewicht				kg	8.7	8.7	12
Buitendeel				PM09SP.UA3	PM12SP.UA3	PM18SP.UL2	PM24SP.UUE
Geluidsniveau	Koelen	Hoog	dB(A)	49	49	53	56
	Afmetingen				mm	717*483*230	717*483*230

Bevat gefluoreerde broeikasgassen. R410a (GWP: 2088)
S: Slaapstand / L: Laag / M: Medium / H: Hoog